

IQS-8140

Transport Blazer

R&D AND MANUFACTURING TESTING – TRANSPORT AND DATACOM



40/43 Gigabit SONET/SDH/OTN test solution for SVT, R&D and manufacturing environments

- Intuitive, feature-rich GUI with multi-user remote access capabilities
- OC-768/STM-256 testing with STS-1/AU-3 granularity
- Supports OTN testing at the OTU3 level including forward error correction (FEC)
- Supports single and dual stage optical channel data unit ODU multiplexing with SONET/SDH and Ethernet mapped client signals
- Offers ODU0 (1.25 Gbit/s) container with Gigabit Ethernet and SONET/SDH client signals for qualifying newly and efficiently mapped transport and datacom services over OTN
- Supports circuit and packet ODUflex testing capabilities for OTN bandwidth optimization
- Multichannel SDT measurements and real-time error/alarm monitoring for SONET/SDH and OTN
- Automated test scripting to improve quality, efficiency and repeatability
- Part of EXFO's unified layer 0/1/2/3/4 testing solution

Platform Compatibility

- IQS-600 Integrated Qualification System



SONET/SDH and OTN Testing Reaches New Level

Increased demand for data and video services continues to put a strain on existing network equipments, driving the need for higher performance metro and core network equipment. As a result, the shift from 10 gigabit- to 40 gigabit-enabled equipment has accelerated over the last year, and will continue at a strong pace, as network operators strive to ensure their next-generation SONET/SDH and OTN networks are scaled to meet these growing bandwidth demands.

This upgrade to 40 Gbit/s transmission creates new challenges for equipment manufacturers, driving the need for 40 Gbit/s test equipment to ensure that new network deployments meet industry standards and offer the required service quality and reliability. EXFO's IQS-8140 Transport Blazer, the industry's most compact 40/43 gigabit lab/manufacturing module, provides advanced SONET/SDH and OTN test functions in a single unit. This module is compatible with the IQS-600 Integrated Qualification System, which also supports 40 Gbit/s physical layer modules such as PMD and OSA, ensuring that users have a truly integrated solution that meets every testing requirement.

SONET/SDH Testing and Troubleshooting

The IQS-8140 Transport Blazer offers a wide range of SONET/SDH test functions ranging from simple bit-error-rate (BER) testing to advanced characterization and troubleshooting procedures. These functions include:

- Mixed and bulk payload generation and analysis from 51.84 Mbit/s to 40 Gbit/s
 - High-order mappings: STS-1/3c/12c/48c/192c/768c and AU-3/AU-4/AU-4-4c/16c/64c/256c
 - Unframed optical signal testing at 40 Gbit/s rate
 - Section/RS, Line/MS and high-order (HO) path overhead manipulation and monitoring
 - Section/RS, Line/MS and high-order (HO) path alarm/error generation and monitoring
 - High-order (HO) pointer generation and monitoring
 - K1/K2 OH byte capture
 - Performance monitoring: G.821, G.828, G.829, M.2100, M.2101
- Frequency analysis and power measurement
 - Frequency offset generation
 - Automatic protection switching (APS) and service disruption time (SDT) measurements
 - Multichannel SDT measurements and real-time error/alarm monitoring for all STS-1/AU-4 channels
 - Round-trip delay (RTD) measurements
 - Intrusive and transparent Through mode analysis
 - Programmable error/alarm injection
 - Independent transmitter and receiver testing
 - Payload block and replace

Optical Transport Network (OTN) Testing and Troubleshooting

Prevalent in 10 Gbit/s networks, OTN has become a necessity for 40 Gbit/s transmission due to its forward error correction capabilities—a critical requirement of service providers worldwide. The IQS-8140 Transport Blazer offers OTN test capabilities (enabled through a software option) for verifying compliancy with ITU-T G.709 standards.

OTN as per ITU-T G.709 has recently introduced two new concepts: ODU0 and ODUflex. ODU0 is a new virtual container of 1.25 Gbit/s bandwidth specifically defined for efficiently mapping Gigabit Ethernet services over OTN. As for ODUflex, it is the most efficient sub-wavelength bandwidth management capability for transport line rates of 10 Gbit/s, 40 Gbit/s and upcoming 100 Gbit/s. ODUflex allows providers to interconnect routers in ways that enable efficient bandwidth growth in steps of 1.25 Gbit/s, eliminating the need to allocate a full fixed-rate ODU container to each connection and allowing service providers to transport efficiently and seamlessly across lower-cost optical infrastructures. The tests include:

- OTU3 (43 Gbit/s) bit rate (framed and unframed)
- Synchronous mapping of SONET/SDH signals within OTN as well as synchronous/asynchronous demapping
- Forward error correction (FEC) testing—error insertion and monitoring
- Service disruption time (SDT) measurements
- Multichannel SDT measurements and real-time error/alarm monitoring for all ODU0 channels
- Round-trip delay (RTD) measurements
- OTU, ODU, OPU overhead manipulation and monitoring
- OTU, ODU (including ODU TCM), OPU layer alarms/errors generation and analysis
- OTU, ODU (including ODU TCM) trace messages
- Intrusive and transparent Through mode analysis
- Multiplexing/demultiplexing of ODU13, ODU23, ODU123, ODU03, ODU013 and ODU0123 with capability of mapping SONET/SDH, Gigabit Ethernet and 10 Gigabit Ethernet client signals into ODU0, ODU1 and ODU2
- ODU0 (1.25 Gbit/s) container with Gigabit Ethernet and SONET/SDH client signals mapping
- ODUflex with SONET/SDH and Ethernet client signal mapping

Product Option Flexibility

The IQS-8140 Transport Blazer provides customers with the flexibility to purchase SONET/SDH-only configurations and upgrade to OTN test functions via software options to meet evolving needs—reducing hardware and/or platform retrofits, and significantly decreasing capital and training expenses.

Powerful Automated Test Scripting

Automation and scripting, traditionally found in manufacturing applications, is gaining momentum in system verification testing environments to facilitate repeatability and improve quality and efficiency. EXFO is committed to addressing manufacturing and system verification test (SVT) needs with its automation features.

The IQS-8140 Transport Blazer includes a wide range of SCPI commands (standard commands for programmable instrumentation), which are powerful enough to provide repeatable testing of complex configurations, yet simple enough to create a 40 gigabit BERT in as little as seven commands. As with all IQS-81xx modules, the IQS-8140 offers an intuitive macro recorder enabling users to easily record test actions and automatically create test scripts in VB.Net.

Part of EXFO's Layer 0/1/2/3/4 Unified Testing Solution

EXFO's IQS-600 platform can house a mix of physical interfaces and protocol modules (SONET/SDH, OTN, Ethernet and Fibre Channel), making it the industry's first truly integrated and unified testing platform. This multilayer, multitechnology modular test platform simplifies upgrades and is the ideal solution for SVT, manufacturing and R&D testing environments.

Combined with the IQS-8130NGE, the IQS-8140 provides a multiservice solution designed to test:

- OTU1/2/3
- SONET/SDH from DS0 to OC-768/STM-256
- Ethernet from 10 Mbit/s to 10 GigE LAN/WAN
- Fibre Channel 1/2/4/10 gigabit

Combined with EXFO's PMD, wavelength and optical spectrum analyzers, the IQS-8140 brings a unique integrated solution addressing all 40 Gbit/s testing requirements from the physical to the transmission layer.

Flexible Remote Access Solution

Through its optional Visual Guardian Lite™ management software, the IQS-8140 Transport Blazer supports remote testing, monitoring and data analysis via standard Ethernet with the same familiar user interface. In addition, users can remotely access the IQS-600 platform with a simple Web browser, a VNC client or Remote Desktop to control any module housed in the platform.



Electrical Interfaces

The following section provides detailed information on all supported electrical interfaces.

SYNCHRONIZATION INTERFACES

	External Clock DS1/1.5M	External Clock E1/2M	External Clock E1/2M	2 MHz (Trigger)
Tx pulse amplitude	2.4 to 3.6 V	3.0 V	2.37 V	0.75 to 1.5 V
Tx pulse mask	GR-499 figure 9.5	G.703 figure 15	G.703 figure 15	G.703 figure 20
Tx LBO preamplification	Typical power dBdsx +0.6 dBdsx (0-133 ft) +1.2 dBdsx (133-266 ft) +1.8 dBdsx (266-399 ft) +2.4 dBdsx (399-533 ft) +3.0 dBdsx (533-655 ft)			
Rx level sensitivity (dynamic range)	TERM: ≤ 6 dB (cable loss only) (at 772 kHz for T1) DSX-MON: ≤ 26 dB (20 dB resistive loss + cable loss ≤ 6 dB) Bridge: ≤ 6 dB (cable loss only)	TERM: ≤ 6 dB (cable loss only) MON: ≤ 26 dB (20 dB resistive loss + cable loss ≤ 6 dB) Bridge: ≤ 6 dB (cable loss only)	TERM: ≤ 6 dB (cable loss only) MON: ≤ 26 dB (resistive loss + cable loss ≤ 6 dB) Bridge: ≤ 6 dB (cable loss only)	≤ 6 dB (cable loss only)
Transmission bit rate	1.544 Mbit/s \pm 4.6 ppm	2.048 Mbit/s \pm 4.6 ppm	2.048 Mbit/s \pm 4.6 ppm	
Reception bit rate	1.544 Mbit/s \pm 50 ppm	2.048 Mbit/s \pm 50 ppm	2.048 Mbit/s \pm 50 ppm	
Intrinsic jitter (Tx)	ANSI T1.403 section 6.3 GR-499 section 7.3	G.823 section 6.1	G.823 section 6.1	G.703 table 11
Input jitter tolerance	AT&T PUB 62411 GR-499 SECTION 7.3	G.823 section 7.2 G.813	G.823 section 7.2 G.813	
Line coding	AMI and B8ZS	AMI and HDB3	AMI and HDB3	
Input impedance (resistive termination)	75 Ω \pm 5 %, unbalanced	75 Ω \pm 5 %, unbalanced	75 Ω \pm 5 %, unbalanced	75 Ω \pm 5 %, unbalanced
Connector type	BNC ^a	BNC ^a	BNC	BNC

REF-OUT INTERFACE

	SONET/SDH	OTN
Parameter	Value	Value
Tx pulse amplitude	600 \pm 200 mVpp	600 \pm 200 mVpp
Transmission frequency	2.48832 GHz	2.68865 GHz
Output configuration	AC coupled	AC coupled
Load impedance	50 Ω	50 Ω
Maximum cable length	1 m	1 m
Connector type	SMA	SMA

NOTE

a. Adaptation cable required for BANTAM.

SONET/SDH and OTN Optical Interfaces

The following section provides detailed information on all supported SONET/SDH and OTN optical interfaces.

OC-768/STM-256/OTU3

Line Coding	NRZ	NRZ-DPSK
Level Tx	0 to 3 dBm	4 to 7.5 dBm
Rx operating range	-5 to 3 dBm	3 to 8 dBm
Transmit bit rate	39.81312 Gbit/s ± 4.6 ppm 43.01841 Gbit/s ± 4.6 ppm (OTU3)	39.81312 Gbit/s ± 4.6 ppm 43.01841 Gbit/s ± 4.6 ppm (OTU3)
Receive bit rate	39.81312 Gbit/s ± 100 ppm 43.01841 Gbit/s ± 100 ppm (OTU3)	39.81312 Gbit/s ± 100 ppm 43.01841 Gbit/s ± 100 ppm (OTU3)
Operational wavelength range	1530 to 1565 nm	1528.77 to 1563.86 nm
Frequency offset generation	39.81312 Gbit/s ± 50 ppm 43.01841 Gbit/s ± 50 ppm	39.81312 Gbit/s ± 50 ppm 43.01841 Gbit/s ± 50 ppm
Measurement accuracy (uncertainty)		
Frequency	±4.6 ppm	±4.6 ppm
Optical power	±2 dB	±1.3 dB
Rx overload	3 dBm	8 dBm
Rx damage level ^a	6 dBm	10 dBm
Jitter compliance	GR-253 (SONET) G.958 (SDH) G.8251 (OTN)	GR-253 (SONET) G.958 (SDH) G.8251 (OTN)
Line coding compliance	G.693 VSR 2000-compliant	NRZ-DPSK
Connector	SC, FC, LC, ST	SC, FC, LC, ST

NOTE

a. In order not to exceed the maximum receiver power level before damage, an attenuator must be used.

SONET/SDH Functional Specifications

SONET		SDH	
Optical Interfaces	OC-768	Optical Interfaces	STM-256
Available wavelengths (nm)	1550	Available wavelengths (nm)	1550
Clocking	Internal, loop-timed, external (BITS), backplane	Clocking	Internal, loop-timed, external (MTS/SETS), 2 MHz, backplane
Mappings		Mappings	
STS-1 SPE	Bulk	AU-3	Bulk
STS-3c/12c/48c/192c/768c, SPE	Bulk	AU-4 AU-4-4c/16c/64c/256c	Bulk Bulk
SONET overhead analysis and manipulation	A1, A2, J0, E1, F1, D1-D12, K1, K2, S1, M0, E2, J1, C2, G1, F2, H4, Z3, Z4, N1, N2	SDH overhead analysis and manipulation	A1, A2, J0, E1, F1, D1-D12, K1, K2, S1, M0, G1, F2, F3, K3, N1, N2, E2, J1, C2, H4
Error Insertion		Error Insertion	
OC-768	Section BIP (B1), line BIP (B2), path BIP (B3), REI-L, REI-P, FAS, bit error	STM-256	RS-BIP (B1), MS-BIP (B2), HP-BIP (B3), MS-REI, HP-REI, FAS, bit error
Error Measurement		Error Measurement	
OC-768	Section BIP (B1), line BIP (B2), path BIP (B3), REI-L, REI-P, FAS, bit error	STM-256	RS-BIP (B1), MS-BIP (B2), HP-BIP (B3), MS-REI, HP-REI, FAS, bit error
Alarm Insertion		Alarm Insertion	
OC-768	LOS, LOF, SEF, AIS-L, RDI-L, AIS-P, LOP-P, PDI-P, RDI-P, ERDI-PCD, ERDI-PPD, ERDI-PSD, UNEQ-P, pattern loss	STM-256	LOS, LOF, OOF, MS-AIS, MS-RDI, AU-AIS, AU-LOP, HP-RDI, ERDI-SD, ERDI-CD, ERDI-PD, HP-UNEQ, pattern loss
Alarm Detection		Alarm Detection	
OC-768	LOS, LOC, LOF, SEF, TIM-S, AIS-L, RDI-L, AIS-P, LOP-P, PDI-P, RDI-P, ERDI-PCD, ERDI-PPD, ERDI-PSD, PLM/SLM-P, UNEQ-P, TIM-P, pattern loss	STM-256	LOS, LOF, LOC, OOF, RS-TIM, MS-AIS, MS-RDI, AU-AIS, AU-LOP, HP-RDI, ERDI-SD, ERDI-CD, ERDI-PD, HP-PLM/SLM, HP-UNEQ, HP-TIM, pattern loss
<i>Frequency alarm on all supported interfaces.</i>			
Patterns		Patterns	
STS-1, STS-3c/12c/48c/192c/768c	2E9-1, 2E11-1, 2E15-1, 2E20-1, 2E23-1, 2E31-1, 1100, 1010, 1111, 0000, 1-in-8, 1-in-16, 32 bit programmable (inverted or non-inverted), bit error	AU-3/AU-4/AU-4-4c/16c/64c/256c	2E9-1, 2E11-1, 2E15-1, 2E20-1, 2E23-1, 2E31-1, 1100, 1010, 1111, 0000, 1-in-8, 1-in-16, 32 bit programmable (inverted or non-inverted), bit error
<i>Pattern loss and bit error generation and analysis supported on all patterns.</i>			

SONET/SDH Functional Specifications (continued)

ADDITIONAL TEST AND MEASUREMENT FUNCTIONS

Power measurements	Supports power measurements, displayed in dBm, for optical interfaces.
Frequency measurements	Supports clock frequency measurements (i.e., received frequency and deviation of the input signal clock from nominal frequency), displayed in ppm and bit/s, for optical and electrical interfaces (external clock).
Frequency offset generation	Supports offsetting the clock of the transmitted signal on a selected interface to exercise clock recovery circuitry on network elements.
Performance monitoring	The following ITU-T recommendations, and corresponding performance monitoring parameters, are supported on the IQS-8140 module.
ITU-T recommendation	Performance monitoring statistics
G.821	ES, EFS, EC, SES, UAS, ESR, SFSR, BM
G.828	ES, EFS, EB, SES, BBE, SEP, UAS, ESR, SESR, BBER, SEPI
G.829	ES, EFS, EB, SES, BBE, UAS, ESR, SESR, BBER
M.2100	ES, SES, UAS, ESR, SESR
M.2101	ES, SES, BBE, UAS, ESR, SESR, BBER
Pointer adjustment and analysis	Generation and analysis of HO/AU pointer adjustments as per GR-253 and ITU-T G.707.
Generation	Analysis
<ul style="list-style-type: none"> • Pointer increment and decrement • Pointer jump with or without NDF • Pointer value 	<ul style="list-style-type: none"> • Pointer increments • Pointer decrements • Pointer jumps (NDF, no NDF) • Pointer value and cumulative offset
Programmable errors/alarms injection	Ability to inject errors/alarms in the following modes: Manual, Constant Rate, Burst, Periodic Burst and Continuous.
Service disruption time (SDT) measurements	The service disruption time test tool measures the time during which there is a disruption of service due to the network switching from the active channels to the backup channels. User-selectable triggers: all supported alarms and errors. Measurements: last disruption, shortest disruption, longest disruption, average disruption, total disruption, and service disruption count.
Round-trip delay (RTD) measurements	The round-trip delay test tool measures the time required for a bit to travel from the IQS-8140 transmitter back to its receiver after crossing a far-end loopback. Measurements are supported on all supported IQS-8140 interfaces and mappings. Measurements: last RTD time, minimum, maximum, average, measurement count (number of successful RTD tests), failed measurement count.
Multichannel testing	Ability to monitor in real-time errors and alarms, and to perform simultaneous SDT measurements for all STS-1/AU-4 channels; a user-defined threshold can also be applied to the SDT measurements for simple pass/fail results for each channel.
APS message control and monitoring	Ability to monitor and set up automatic protection switching messages (K1/K2 byte of SONET/SDH overhead).
Synchronization status	Ability to monitor and set up synchronization status messages (S1 byte of SONET/SDH overhead).
Signal label control and monitoring	Ability to monitor and set up payload signal labels (C2 byte of SONET/SDH overhead).
Through mode	Ability to perform intrusive and transparent Through mode analysis of any incoming optical line (OC-768/STM-256, OTU3).
Payload block and replace	Ability to terminate and analyze a specific high-order path element and replace it with a PRBS pattern on the TX side.
K1/K2 OH byte capture	Ability to capture K1/K2 OH byte value transitions.

OTN Functional Specifications

OTN	
Standards compliance	ITU-T G.709, ITU G.798, ITU G.872
Interfaces	OTU3 (43 Gbit/s)
OTU Layer	
Errors	OTU-FAS, OTU-MFAS, OTU-BEI, OTU-BIP-8
Alarms	LOF, OOF, LOM, OOM, OTU-AIS, OTU-TIM, OTU-BDI, OTU-IAE, OTU-BIAE
Traces	64-bytes Trail Trace Identifier (TTI) as defined in ITU-T G.709
ODU TCM Layer	
Errors	TCMi-BIP-8, TCMi-BEI (i = 1 to 6)
Alarms	TCMi-LTC, TCMi-TIM, TCMi-BDI, TCMi-IAE, TCMi-BIAE
Traces	64-bytes Trail Trace Identifier (TTI) as defined in ITU-T G.709
ODU Layer	
Errors	ODU-BIP-8, ODU-BEI
Alarms	ODU-AIS, ODU-OCI, ODU-LCK, ODU-TIM, ODU-BDI, ODU-FSF, ODU-BSF, ODU-FSD, ODU-BSD
Traces	Generates 64-bytes Trail Trace Identifier (TTI) as defined in ITU-T G.709
FITL ^a	As defined in ITU-T G.709
OPU Layer	
Alarms	OPU-PLM, OPU-CSF, OPU-AIS
Payload type (PT) label	Generates and displays received PT value
GMP errors	Cm CRC-8, CnD CRC-5
Forward Error Correction (FEC)	
Errors	FEC-Correctable (Codeword), FEC-Uncorrectable (Codeword), FEC-Correctable (Symbol), FEC-Correctable (Bit), and FEC-Stress (Codeword)
ODU Multiplexing	
Mappings	ODU13, ODU23, ODU123, ODU0, ODUflex
Alarms	OPU-MSIM, ODU-LOFLOW
Client	PRBS pattern, STS-3c/12c/48c/192c/768c, AU-4-4c/16c/64c/256c
ODU0	
Muxing	ODU0 into ODU3, ODU0 into ODU13, ODU0 into ODU13
Client types	Pattern, OC-3/STM-1, OC-12/STM-4, GigE using GFP-T
GFP-T errors	SB Correctable, SB Uncorrectable, 10B_ERR
ODUflex	
Muxing	ODUflex into ODU3
Client types	Ethernet using GFP-F or pattern for constant bit rate (CBR)
GFP-F alarms	Client forward defect indication (FDI), client reverse defect indication (RDI), client defect clear indication (DCI)

NOTE
a. Fault type and fault location.

OTN Functional Specifications (continued)

ADDITIONAL FUNCTIONS

Service disruption time (SDT) measurements	The service disruption time test tool measures the time during which there is a disruption of service due to the network switching from the active channels to the backup channels. User-selectable triggers: all supported alarms and errors. Measurements: last disruption, shortest disruption, longest disruption, average disruption, total disruption and service disruption count.
Round-trip delay (RTD) measurements	The round-trip delay test tool measures the time required for a bit to travel from the IQS-8140 transmitter back to its receiver after crossing a far-end loopback. Measurements are supported on all supported IQS-8140 interfaces and mappings. Measurements: last RTD time, minimum, maximum, average, measurement count (number of successful RTD tests), failed measurement count.
Multichannel testing	Ability to monitor in real-time errors and alarms, and to perform simultaneous SDT measurements for all ODU0 channels; a user-defined threshold can also be applied to the SDT measurements for simple pass/fail results for each channel.

Additional Features

Scripting	Wide range of SCPI commands powerful enough to provide repeatable testing of complex configuration, yet simple enough to create a 40 gigabit BERT in as little as seven commands. The IQS-8140 also includes an intuitive macro recorder enabling users to easily record test actions and automatically create test scripts in VB.Net.
Reports	Supports generation of test reports in .html, .csv, .txt, .pdf formats. Contents of reports are customizable by the user.
Power-up and restore	In the event of a power failure to the unit, the active test configuration and test logger are saved and restored upon bootup.
Store and load configurations	Ability to store and load test configurations to/from non-volatile memory.
Alarm hierarchy	Alarms are displayed according to a hierarchy based on root cause. Secondary effects are not displayed. This hierarchy serves to facilitate alarm analysis.
Configurable test views	This allows users to customize their test views, i.e., to dynamically insert or remove test tabs/windows, in addition to creating new test windows, so as to accurately match their testing needs.
Configurable test timer	Provides the ability for a user to set pre-defined test start and stop times.
Remote access	Available with Windows-based remote management software known as Visual Guardian Lite (optional software package). This allows users to remotely monitor and control the IQS-8140 module via standard Ethernet connection.

Additional Specifications

IQS-8140

SONET/SDH 40 Gbit/s and OTN 43 Gbit/s (optical rates)

Test Interfaces

OTN: OTU3 (43 Gbit/s)

SONET: OC-768

SDH: STM-256

GENERAL SPECIFICATIONS

	IQS-8140
Weight	2.8 kg (6.1 lb)
Size (H x W x D)	125 mm x 189 mm x 283 mm (4 15/16 in x 7 7/16 in x 11 1/8 in)
Temperature	
operating	0 °C to 40 °C (32 °F to 104 °F)
storage	-40 °C to 60 °C (-40 °F to 140 °F)

ORDERING INFORMATION

IQS-8140-XX-XX-XX-XX-XX

Model

IQS-8140-**NRZ** = SONET/SDH test module with 40/43 Gbit/s, 1550 nm, NRZ 2 km transponder
 IQS-8140-**DPSK** = SONET/SDH test module with 40/43 Gbit/s, tunable DPSK transponder

Connector

89 = FC/UPC
90 = ST/UPC
91 = SC/UPC
101 = LC/UPC

Software options

SONET = SONET-BASE-SW
SDH = SDH-BASE-SW
SONET-SDH = Combined SONET/SDH

Other software options

00 = Without other options
ODUMUX = ODU multiplexing functionality ^a
ODU0 = ODU0 mapping ^b
ODUFlex = ODUflex functionality ^b
OTU3 = OTN 43 Gbit/s (G.709/OTU3) ^c
OTN-INTR-THRU = Intrusive OTN Through mode ^a
INTR-THRU-MODE = SONET/SDH intrusive Through mode
MULTI-CH-SDT = Multichannel SDT measurements

Rate option ^d

40G = 40 Gbit/s (OC-768/STM-256)

Example: IQS-8140-NRZ-91-SONET-40G-OTU3

NOTES

- a. Must be combined with the OTU3 option.
- b. Must be combined with ODUMUX option.
- c. Included as standard for IQS-8140-DPSK.
- d. Included as standard for IQS-8140-NRZ and IQS-8140-DPSK.

EXFO Corporate Headquarters > 400 Godin Avenue, Quebec City (Quebec) G1M 2K2 CANADA | Tel.: +1 418 683-0211 | Fax: +1 418 683-2170 | info@EXFO.com

Toll-free: +1 800 663-3936 (USA and Canada) | www.EXFO.com

EXFO America	3400 Waterview Parkway, Suite 100	Richardson, TX 75080 USA	Tel.: +1 972 761-9271	Fax: +1 972 761-9067
EXFO Asia	100 Beach Road, #22-01/03 Shaw Tower	SINGAPORE 189702	Tel.: +65 6333 8241	Fax: +65 6333 8242
EXFO China	36 North, 3 rd Ring Road East, Dongcheng District Room 1207, Tower C, Global Trade Center	Beijing 100013 P. R. CHINA	Tel.: + 86 10 5825 7755	Fax: +86 10 5825 7722
EXFO Europe	Omega Enterprise Park, Electron Way	Chandlers Ford, Hampshire S053 4SE ENGLAND	Tel.: +44 23 8024 6810	Fax: +44 23 8024 6801
EXFO NetHawk	Elektronikkatie 2	FI-90590 Oulu, FINLAND	Tel.: +358 (0)403 010 300	Fax: +358 (0)8 564 5203
EXFO Service Assurance	270 Billerica Road	Chelmsford, MA 01824 USA	Tel.: +1 978 367-5600	Fax: +1 978 367-5700

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at <http://www.EXFO.com/specs>

In case of discrepancy, the Web version takes precedence over any printed literature.