

AXS-200

HANDHELD MODULAR PLATFORM



As part of the SharpTESTER line LAN applications, this tool is designed for access network testing

KEY FEATURES

One-touch test start/stop

One user interface for all SharpTESTER series modules

Flexible architecture adapting to evolving customer requirements

Rugged, weather-proof design

Easy to use, even for technicians who are inexperienced or unfamiliar with specific applications

Fast and clear pass/fail results on a transfective graphical color display

APPLICATIONS

AXS-200 / 600 Series : Copper, DSL and Triple-Play testing

AXS-200 / 800 Series : Installation and Maintenance of Ethernet networks

A MULTILAYER, MULTIMEDIUM TEST SOLUTION

This three module series applies to optics, Ethernet and copper/DSL/triple-play. With respect to optics, it offers physical-layer testing within fiber access links. It also ensures installation and maintenance testing for Ethernet circuits. As for copper/DSL/triple-play, it enables complete local loop testing, xDSL QoS assessment as well as Ethernet testing for triple-play services.

FLEXIBLE CONNECTIVITY

The unit has a fiber inspection probe (FIP) port, an RJ-45 port as well as a USB A/B port. The USB port enables easy file transfers and software upgrades.

SPECIFICATIONS	
Display	89 mm (3.5 in) LCD, 320 x 240, QVGA, advanced TFT
Interfaces	USB host/client, RJ-45 Ethernet 10/100, video fiber inspection probe port
Storage	Internal: 512 MB; USB: 1 GB, 2 GB and more
Battery	Smart rechargeable Li-Ion
Power supply	15-24 VDC, 40 W minimum

GENERAL SPECIFICATIONS		
Temperature operating	-10 °C to 50 °C	(14 °F to 122 °F)
Temperature storage ^a	-40 °C to 70 °C	(-40 °F to 158 °F)
Size (H x W x D)	241 mm x 109 mm x 38 mm	(9 1/2 in x 4 5/16 in x 1 1/2 in)
Weight	0.47 kg	(1.0 lb)
Relative humidity	0 % to 93 %, non-condensing	
Warranty	1 year	

Note

a. Maximum of 60 °C (140 °F) for the internal battery.

ACCESSORIES	
GP-10-072	Semi-rigid carrying case
GP-10-074	Rigid carrying case AXS-200
GP-2016	RJ-45 LAN cable (10 feet)
GP-2019	USB microdrive (1 GB)

ORDERING INFORMATION

AXS-200-XX-XX

<p>Model ■ AXS-200 = SharpTESTER</p> <p>Probe option ■ 00 = Without probe FP4S = Inspection probe (400x) FP4D = Inspection probe (200x/400x)</p> <p>Example: AXS-200-FP4D-FPS</p>	<p>■ Platform software option FPS = With FIP software</p>
---	--

EXFO Headquarters > Tel.: +1 418 683-0211 | Toll-free: +1 800 663-3936 (USA and Canada) | Fax: +1 418 683-2170 | info@EXFO.com | www.EXFO.com

EXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.

EXFO is certified ISO 9001 and attests to the quality of these products. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at www.EXFO.com/specs.

In case of discrepancy, the Web version takes precedence over any printed literature.